



25 l



50 l

SPECIFICATIONS	DSS 25 A	DSS 50 A
Power input	max. 1,400 W	max. 1,400 W
Rated voltage	230 V ~	230 V ~
Tank volume (max.)	25 l	50 l
Dust volume (net)	20 l Dust	45 l Dust
Max. air flow	61 l/s	61 l/s
Max. vacuum	248 mbar	248 mbar
Dimensions L x B x H (mm)	457 x 400 x 535	580 x 470 x 640
Weight	12.7 kg	17.7 kg
Order no.	09915000	09916000

Supplied: 5 m hose (Ø 35 mm), universal-adapter, nozzle for floor and crevices, handle tube with air switch, 2 suction tubes (plastic), velcro strip, holder for accessories

Industrial vacuum cleaner DSS 25 A and DSS 50 A

The compact wet and dry cleaners

USE:

- Vacuuming of dust (dry) and sludges (wet)
- Cleaning of construction sites and cars

FEATURES:

- Automatic filter cleaning (electromagnetic pulse)
 - cleaning of the filter, working without, complete dedusting of the cartridges
- Electronically controlled soft start with deferred run-down switching
- Power socket with automatic switch-on for attached machines
- Flow rate indicator – optical monitoring of the suction performance
- Consistently high flow rate – increases filter life, reduction of time and costs
- Water recognition with sensor disconnection
- Two polyester filter cassettes – high efficiency, durable, easy to clean
- Filter surface 8,600 cm² – high constant suction performance
- Compact design – smaller height, same volume
- Special-plastic tank – low centre of gravity, easy cleaning of walls
- Storage tray for accessories or machines
- Hose connection with bayonet and twist balancing
- Hose ends interchangeable – easy hose extension, dust-free transport

